

“Installation You’ll Hardly Notice...”

With Energy Savings And Less Hassles
You Will Notice!



Safer For Your Building...

No open flames, hot asphalt, or solvents on your roof

Saves Energy...

Exceeds the minimum reflectivity/emissivity requirements for ENERGYSTAR™ qualification—to save you money (white only)

Consistent Quality...

Factory-applied adhesive eliminates guesswork by the installer, resulting in uniform application and less chance of adhesive-related wind uplift problems

Environmentally Friendly...

Eliminates conventional adhesives (and the volatile organic compounds contained in them) that can cause safety and environmental issues

Peace Of Mind

Your choice of fully self-adhered (with 10 year manufacturer's guarantee) or self-adhered with heat-welded seams (with 15 year manufacturer's guarantee)

Color Options...

Comes in your choice of white or tan, to match your color scheme

EverGuard®
Freedom™ TPO
Self-Adhering Roofing Systems



**Quality You Can Trust
Since 1886...
from North America's
Largest Roofing
Manufacturer**

*“Great Performance...
Less Hassles!”*

EverGuard® Freedom™ TPO Self-Adhering Roofing Systems

Easy Installation...

- Just lay out the sheet, pull off the release film, and attach to substrate!

Quick Application...

- No Waiting...For adhesives to dry or to become contaminated by airborne particles
- Ready To Install...Right from the factory
- Faster...Up to 5 times faster than water-based adhesives and up to 3 times faster than solvent-based adhesives (depending on outside temperature)

Especially Ideal For Re-Covers...

- UL Class A...The highest rating possible
- Multiple Approvals...Including Dens Deck primed and wood fiber board

Occupant-Friendly...

- No Fumes... From either hot asphalt or solvents
- Less Disruption...To normal business activity
- No Hassles...Having to evacuate a building due to odor

Low/No Investment Needed...

- Conserves Cash...Hot air or generating equipment is optional (i.e., only needed when installing Freedom TPO HW - “heat weldable”)

Complete Accessory Line...

- Better Protection...A complete line of pre-molded, self-adhering accessories
- Saves Time... eliminates field construction that can result in a faulty or damaged detail

Superior Uplift Protection...

- Thoroughly Tested...At the industry’s leading test facility and passed a wind uplift rating of 105 psf

Nominal Product Specifications

(All specs pertain to both versions of Freedom TPO)

Freedom TPO SA (self-adhered seams)

Freedom TPO HW (heat-weldable seams)

Roll length	50 ft (15.2 m)
Roll width	60 in (1.5 m)
Approx. roll weight	72 lbs (32.7 kg)
Square feet per roll	250 sq ft (23.2 sq m)

Easy, Simple Installation!*



Step 1
Sweep dirt from substrate



Step 2
Unroll and position product



Step 3
Remove release film (left) and
adhere membrane (right)



Step 4
Roll edges, seams, field of roof

*Photos depict installation of self-adhered product;
heat-welded product installation differs slightly



1-888-2HERMAN
WWW.2HERMAN.COM